Dual Stacking Broadband Subscribers Lessons Learned

Aka. IPv6 Herpa Derpa in Access Networks (thanks Job)



Warcraft

AS5607 Overview

- Primarily residential broadband
- ~6 million fixed-line subscribers
- On-net (LLU):
 - ~80% ADSL2+
 - PPPoE
- Off-net:
 - ~20% VDSL2
 - IPoE
- Alcatel-Lucent[^]WNokia 7750SR as BRAS/BNG





IPv6 Deployment Strategy

- Native dual-stack service
- Link-local WAN addressing only
- /39 per service per BNG
- Single /56 allocated via DHCPv6 PD
 - Dynamic
 - Although "sticky", unless the client sends a RELEASE or changes DUID
- SLAAC running on CPE for LAN address assignment
 - Using just the first /64 for now
- ULA on LAN side



Enablement

- Pre-requisites:
 - All BNGs capable
 - P&T, CDN dual stacked for comparable v4 routes
 - CPEs upgraded to v6 capable firmware
- Granular, per-user enablement
- Targeted enablement. Not geographic/BNG based.
 - Service Type: LLU (PPP) vs Off-net (IPoE)
 - CPE type/version
 - Ability to exclude misbehaving CPEs/devices.
- RADIUS controlled
 - DHCPv6 pool name returned in RADIUS Access-Accept.



Enablement

- Started soft-launch end of July 2015
- Up to ~1M by September
- Paused for 6 months:





Enablement Paused. Why?

- Anycast platform load doubled
 - RADIUS Authentication
 - Recursive DNS
- RDNSS
 - Each host lookup now sends A & AAAA queries
 - We expected this, and capacity planned for it
 - Load increase didn't follow our enablement plan linearly
 - AAAA queries were triggered by the CPE firmware upgrade, not IPv6 WAN enablement:
 - Windows & OSX will send AAAA queries when assigned a non-link-local address. Eg. ULA
 - Android and Chrome will not



Completely Tangential Side-Note

- Don't expect Chrome to work on your private ULA LAN/Intranet:
- Yes, that's Google's public v6 DNS server hardcoded in as a connectivity check

52 Ð υ s/host_resolver_impl.cc 2048 } 2049 2050 HostResolverImpl::Key HostResolverImpl::GetEffectiveKeyForRequest(2051 const RequestInfo& info) const { HostResolverFlags effective flags = 2052 2053 info.host resolver flags() | additional resolver flags ; 2054 AddressFamily effective address family = info.address family(); 2055 2056 if (info.address family() == ADDRESS FAMILY UNSPECIFIED) { 2057 if (ipv6 probe monitoring) { 2058 base::TimeTicks start time = base::TimeTicks::Now(); 2059 // Google DNS address. 2060 const uint8 kIPv6Address[] = 2061 { 0x20, 0x01, 0x48, 0x60, 0x48, 0x60, 0x00, 0x00, 2062 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x88, 0x88 }; 2063 IPAddressNumber address(kIPv6Address, 2064 kIPv6Address + arraysize(kIPv6Address)); 2065 bool rv6 = IsGloballyReachable(address); 2066 2067 UMA HISTOGRAM TIMES("Net.IPv6ConnectDuration", 2068 base::TimeTicks::Now() - start time); 2069 if (rv6) { UMA HISTOGRAM BOOLEAN("Net.IPv6ConnectSuccessMatch", 2070 2071 default address family == ADDRESS FAMILY UNSPECIFIED); 2072 } else { 2073 UMA HISTOGRAM BOOLEAN("Net.IPv6ConnectFailureMatch", 2074 default address family != ADDRESS FAMILY UNSPECIFIED); 2075 2076 effective address family = ADDRESS FAMILY IPV4; effective flags |= HOST RESOLVER DEFAULT FAMILY SET DUE TO NO IPV6; 2077 2078 2079 } else { effective address family = default address family ; 2080

Subscriber Authentication

• PPPoE

- Authentication based on PADI
- Remote-ID/Circuit-ID (Broadband Forum TR-101)
- Ignore CHAP username/password
- PPP session comes up before DHCPv6 PD



9

Subscriber Authentication

• IPoE

- DHCPv4 Option 82.2 (Remote-ID) inserted by the Access Node
- BT/Openreach do not support the DHCPv6 equivalent on their entire VDSL footprint. (Huawei ISAMs do, but ECI don't)
- Nokia 7750 SR feature "IPoE Linking"
 - Within 10 seconds of v4 session establishment
 - Not 100% reliable.
- Python cache





Subscriber Authentication With DHCPv6 LDRA

- DHCPv4 Option 82.1 Circuit-ID doesn't exist
 - Replaced with Option 18: Interface-ID
- Remote-ID: Option 37
 - Prepended with an extra 4 bytes for Enterprise-ID
 - Gets copied into the same RADIUS Remote-ID attribute
 - Extra logic required in RADIUS to know when an Access-Request has been triggered by DHCPv4 or DHCPv6

3. The Relay Agent Remote-ID Option

This option may be added by DHCPv6 relay agents that terminate switched or permanent circuits and have mechanisms to identify the remote host end of the circuit.

The format of the DHCPv6 Relay Agent Remote-ID option is shown below:

0	1	2	3	
0 1 2 3 4 5 6 7 8	9012345	6789012	345678901	
+-	+_+_+_+_+_+	+_+_+_+_+_+_+_+	-+	
OPTION_REMOTE_ID		option	option-len	
+-				
enterprise-number				
+-				
. remote-id				
+-				
option-code	OPTION_REMOTE_	_ID (37)		
option-len		• •	f the remote-id	
	field. The mi	inimum option-le	en is 5 octets.	



CPE

- 8 different CPEs. Majority have been developed in-house.
 - (Both a blessing and a curse)
- DHCPv6 Client Not Backing Off
 - RFC3315 specifies a back-off algorithm when an ADVERTISE hasn't been received, but not if an ADVERTISE is received with NoPfxAvailable
 - A lot of extra RADIUS Authentication load
 - Python script to block requests until we were ready to enable v6
- Stateful Firewall or not?
 - Allow unsolicited inbound IPSec, as per RFC6092
 - Lack of IGD:2 support. No UPnP functions for IPv6 firewall manipulation.
- Other devices with lack of IPv6 support
 - Wifi Boosters



CDN etc.

- Google's v6 report showed UK's v6 with +10ms latency
- Google Global Cache switch FDB entries would time out
 - GGC only send unsolicited Neighbor Advertisements
 - Eg. They don't respond to Neighbor Solicits
 - Enabled 'ipv6 nd na glean'
- Geolocation
 - \$CDN reported ::/0 as being in the USA
- Logfiles
 - What happens when a tool expects a v4 dotted decimal address but receives 2001:db8:f00:baa::1?
 - SEGFAULT is not the correct answer



Bonus Anecdotes

- More CPE fun:
 - Pfsense wouldn't send a DHCPv6 SOLICIT until it received an RA.
 - Firmware upgrade broke 6in4 tunnels. Eg. Hurricane Electric.
- \$Bank and their F5s
 - F5 & \$Bank response: *Sky is unique and the only one affected, it must be your fault.*
 - Silently discard any DNS query for an unknown record, instead of returning NXDOMAIN. Eg. AAAA queries.
 - This is considered by F5 to be 'best practice'.
 - Our recursors started blacklisting their authoritative servers, for all queries.
 - Quote from our vendor: "the immediate answer that I got from the engineers contained some swearing and some funny stuff but basically says that what F5 is doing is horrible and is more like a 'worst practice'"



() www.itpro.co.uk/broadband/27034/sky-broadband-back-online-after-morning-outage





- Finally something good(ish):
 - 6PE and VPNv6 were on different route-reflectors

WRITTEN BY Nicole Kobie

NEWS

2 Aug, 2016

Fibre customers were knocked offline for two hours this morning

Sky has apologised for "making Tuesday harder than it already is" with a nationwide fibre broadband outage this morning.

Early this morning, Sky customers started to report outages. By 8.30am, the company admitted that Sky Fibre and Sky Fibre Unlimited customers were "having issues browsing" across the country, saying that engineers were looking into the issue.

It has since said that fibre customers should be back online.

Sky has not yet revealed the cause of the fault, but analysts at ThinkBroadband pointed the blame on a routing issue for IPv4 traffic, as IPv6 traffic appeared to still be working.

"The use of IPv6 versus IPv4 is usually totally transparent to many users and Sky Broadband is biggest provider offering a dual stack configuration for users, to the extent that we see lots of speed tests from Sky users on IPv6," noted Andrew Ferguson on the site.





Ö	. ♣ Follow	
\mathbf{M}		

But no one else is deploying #IPv6



